



SKU	: 117CW9273000
Housing Material	: Aluminum Die Cast
Housing Color	: White
Luminaire Dimension [mm]	: Ø110x77mm
Cut-Out [mm]	: Ø100mm
Optic	: Reflector
Reflector Color	: Specular Aluminium
Beam Angle [deg]	: 30°
LED Power [W]	: 9W
System Power [W]	: 11.5W
Luminous Flux [lm]	: 705lm
System Efficiency [lm/W]	: 61lm/W
CCT [K]	: 2700K
CRI [Ra]	: 90
Chromaticity Tolerance	: 3 MacAdam
Mains Voltage [VAc]	: N/A
Power Supply	: Separate Available
Nominal Current [mA]	: 500mA
Forward Voltage [V]	: 18.4V
Ambient Temperature [degC]	: 35°C
Ingress Protection	: IP43/IP20

Light Source Energy Class	: F
Light Source Identifier	: BXRE-27G0800-D-73
Lifetime/Failure Rate [h]	: 50000h
Electrical Safety Class	: Class II
Net Weight [Kg]	: 0.42Kg
Certificates/Declarations	: CE/UKCA
Warranty [Y]	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.
Technical data can change without prior notice.