



<b>SKU</b>	: 147DB92740BGF0
<b>Housing Material</b>	: Aluminum Die Cast
<b>Housing Colour</b>	: Black (RAL 9005)
<b>Luminaire Dimension [mm]</b>	: Ø98mm
<b>Cut-Out [mm]</b>	: Ø90mm
<b>Optic</b>	: Reflector
<b>Reflector Colour</b>	: Black High Gloss
<b>Beam Angle [deg]</b>	: 40°
<b>System Power [W]</b>	: 10.5W
<b>Luminous Flux [lm]</b>	: 790lm
<b>System Efficiency [lm/W]</b>	: 75lm/W
<b>Light Source</b>	: 927 (2700K / CRI90)
<b>CCT [K]</b>	: 2700K
<b>CRI [Ra]</b>	: 90
<b>Chromaticity Tolerance</b>	: 3 MacAdam
<b>Mains Voltage [VAc]</b>	: 220-240V / 50-60Hz
<b>Power Supply</b>	: Included ON/OFF
<b>Nominal Current [mA]</b>	: 250mA
<b>Forward Voltage [V]</b>	: 34V
<b>Ambient Temperature [degC]</b>	: 35°C
<b>Ingress Protection</b>	: IP20

<b>Light Source Energy Class</b>	: F
<b>Light Source Identifier</b>	: CLU028-1204C4-273H5M3-F1
<b>Lifetime/Failure Rate [h]</b>	: 50000h
<b>Electrical Safety Class</b>	: Class II
<b>Net Weight [Kg]</b>	: 0.45Kg
<b>Certificates/Declarations</b>	: CE/UKCA
<b>Warranty [Y]</b>	: 5Y

All rated values @ ambient temperature of 25° C. Electric and photometric values are initially subject to a tolerance of +/- 10%. Tolerance of color temperature +/- 150K.  
Technical data can change without prior notice.