

OCULUS S

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

IP

Mounting

Indoor

20

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT

941lm

12W

36V

90

2700K / 3000K / 4000K

Optics

Light controller type

Lens: 15°/24°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V/100-277V/100-240V


0.5C/0.9C/0.98C

300mA


On/Off/DALI DT6/0-10V/Triac




OCULUS-S



OCULUS-S-12B-S1



OCULUS-S-12B-S2



OCULUS S

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

IP

Mounting

Indoor

20

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT

662~730Lm

12W

36V

90

2700K-6000K

Optics

Light controller type

Lens: 15°/24°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V


0.9C/0.5C

300mA


DALI DT8/Bluetooth+2.4G Dimming
and color djustment




OCULUS-S



OCULUS-S-12B-S1



OCULUS-S-12B-S2



OCULUS S

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Material

Colour

Spotlights

Diecast Aluminum

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

IP

Mounting

Indoor

20

Recessed

Light Source

Luminous flux

Power

Typical voltage

CRI

CCT

622Lm

12W

36V

90

1800K-5000K

Optics

Light controller type

Lens: 15°/24°/36°/50°

Driver

Input voltage(V)

Power Factor

Output current

Dimming Type

220-240V


0.9C

300mA


DALI DT8




OCULUS-S



OCULUS-S-12B-S1



OCULUS-S-12B-S2



OCULUS S

Indoor lighting fixtures, environmentally friendly SMD chips.
Good heat dissipation structure design.
Elegant appearance and concise.



Luminaire

Product type

Spotlights

Material

Diecast Aluminum

Colour

Sandy black , Sandy white ,
Matte silver , Matte Brass ,
Matte Bronze

Installation

Environment

Indoor

IP

44/65

Mounting

Recessed

Light Source

Luminous flux

855Lm

Power

12W

Typical voltage

36V

CRI

90

CCT

2700K / 3000K / 4000K

Optics

Light controller type

Lens: 15°/24°/36°/50°

Driver

Input voltage(V)

220-240V/85-265V

Power Factor

0.9C

Output current


250mA

Dimming Type

On/Off



OCULUS-S



OCULUS-S-12B-S1



OCULUS-S-12B-S2

